

**ZETA**

## HOW TO SELECT A TYRE

Tyre size and maximum speed of the vehicle.  
The maximum load capacity per axle (Load index).  
Your style driving and road condition.

## MOUNTING & DISMOUNTING

Only get trained people mounting and dismounting your tyres.

## TYRE PRESSURE


For safe drive, it is extremely important to drive with the right pressure.

## CHECK FOLLOWING ITEMS IN REGULAR WAY

Tread pattern  
Unusual wear, tread groove separation, bulges, etc.

Sidewall  
Impact, bulges, ozone cracking, vehicle contact damage etc.

Pressure  
The inflated pressure will be changed during long driving and changed circumstances temperature.



DISTRIBUTED BY

[www.sd-international.com](http://www.sd-international.com)

These data can be changed by the manufacturer without prior notice and differently applied by regions.

Printed on Oct. 2025



[www.zeta-tyres.com](http://www.zeta-tyres.com)



# WHY ZETA

## OUTSTANDING VALUE BACKED BY WORLD LEADING INDUSTRY 4.0 MANUFACTURING.

State of the art manufacturing facility, only opened in 2008.

Design engineering from Europe, using the most up to date design technology available.

Over 600 size already available, with more serial to be introduced in near future.

All size tested & approved according to Regulation of (EU) No.2020/740 and registered by EPREL regarding wet grip, rolling resistance, external noise, snow grip & ice grip which stipulated by European Union.

Certification for each market are available.

Full coverage of Quality Warranty and Products Liability Insurance.

Exclusive distribution arrangements available.

Direct factory program, ensuring regular steady supply and competitive price.

Full market support to develop your business.





ZETA

PASSENGER SUMMER TYRE

A row of Zeta passenger summer tires displayed against a black background. The top row includes Acceni, Alventi, Impero, ZTR50, ZTR20, and ZTR18. The bottom row includes ZTR10, ZTR08, Toledo, Zivaro A/T, Forttrak M/T, and Artoria EV. A red 'New' tag is placed next to the Impero tire in the top row.

ACCENI ALVENTI IMPERO ZTR50 ZTR20 ZTR18

ZTR10 ZTR08 TOLEDO ZIVARO A/T FORTRAK M/T ARTORIA EV

**ACCENi**

- Comfortable Ride**  
A brand new design, introduced & developed to enhance driving pleasure.
- Safe Drive**  
To provide safety & sustainability in U-UHP tyres sector. Ideal choice for sporty vehicles & ultimate high-performance city SUV.
- Precise Handling**  
Excellent balancing performance between dry handling for sporty drivers and everyday safety in wet conditions.
- Enhanced Durability**  
Complex compounds technology ensure ruggedness in tread blocks.

Icons: shield, sun, steering wheel, speaker, water droplet, double arrow, car silhouette, car silhouette with checkmark.

<b>ACCENi</b>							
Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)
285/50R20	116 XL	V	240	149	340	44	1250
215/45ZR18	93 XL	W	270	168	340	49	650
295/45ZR20	110	Y	300	186	300	44	1060
225/40ZR18	92 XL	Y	300	186	340	49	630
275/40ZR18	103 XL	Y	300	186	340	49	870
285/40ZR20	108 XL	W	270	168	340	49	1000
295/40ZR20	110 XL	Y	300	186	340	49	1060
245/40ZR21	100 XL	W	270	168	340	49	700
265/40ZR21	105 XL	Y	300	186	340	49	925
275/40ZR22	108 XL	Y	300	186	340	49	1000
285/40ZR22	110 XL	W	270	168	340	49	1060
295/40ZR22	112 XL	W	270	168	340	49	1120
325/40ZR22	114	Y	300	186	300	44	1180
245/35ZR18	92 XL	Y	300	186	340	49	630
225/35ZR20	93 XL	W	270	168	340	49	600
275/35ZR21	103 XL	Y	300	186	340	49	875
295/35ZR21	107 XL	Y	300	186	340	49	975
305/35ZR21	109 XL	Y	300	186	340	49	1030
275/35ZR22	104 XL	Y	300	186	340	49	900
315/35ZR22	111 XL	Y	300	186	340	49	1090
325/35ZR22	110	Y	300	186	300	44	1060
255/30ZR20	92 XL	Y	300	186	340	49	630
315/30ZR22	107 XL	Y	300	186	340	49	975
							2149



## ALVENTI

- Modern asymmetric design, outer longitudinal grooves to reduce aquaplaning risk, leading to safety on wet conditions.
- Inner inclined grooves to increase lateral grip and reduce noise, leading to outstanding traction & riding comfort.
- Improved lateral rigidity at high speed with high levels of handling.




## ALVENTI

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)
195/65R15	91	V	240	149	300	44	615	1356
195/65R15	95 XL	H	210	130	340	49	690	1521
205/65R15	94	H	210	130	300	44	670	1477
205/65R16	95	V	240	149	300	44	690	1521
185/60R15	88 XL	V	240	149	300	44	560	1235
195/60R16	89	H	210	130	300	44	580	1279
205/60R16	96 XL	V	240	149	340	49	710	1565
215/60R16	95	V	240	149	300	44	690	1521
225/60R16	98	H	210	130	300	44	750	1653
195/55R15	85	V	240	149	300	44	515	1135
195/55ZR16	91 XL	W	270	168	340	49	615	1356
205/55ZR16	91	W	270	168	300	44	615	1356
215/55ZR16	97 XL	W	270	168	340	49	730	1609
225/55ZR16	99 XL	W	270	168	340	49	775	1709
205/55ZR17	95 XL	W	270	168	340	49	690	1521
215/55ZR17	98 XL	Y	300	186	340	49	750	1653
225/55ZR17	101 XL	W	270	168	340	49	825	1819
235/55ZR17	103 XL	Y	300	186	340	49	875	1929
225/55ZR18	102 XL	W	270	168	340	49	850	1874
195/50R15	82	V	240	149	300	44	475	1047
205/50ZR17	93 XL	Y	300	186	340	49	650	1433
215/50ZR17	95 XL	Y	300	186	340	49	690	1521
225/50ZR17	98 XL	Y	300	186	340	49	750	1653
235/50ZR17	100 XL	W	270	168	340	49	800	1764
195/45R16	84 XL	V	240	149	340	49	500	1102
215/45ZR16	86	W	270	168	300	44	530	1168
205/45ZR17	88 XL	Y	300	186	340	49	560	1235
215/45ZR17	91 XL	Y	300	186	340	49	615	1356
225/45ZR17	94 XL	W	270	168	340	49	670	1477
235/45ZR17	97 XL	Y	300	186	340	49	730	1609
225/45ZR18	95 XL	Y	300	186	340	49	690	1521
235/45ZR18	98 XL	Y	300	186	340	49	750	1653
245/45ZR18	100 XL	W	270	168	340	49	800	1764
255/45ZR18	103 XL	Y	300	186	340	49	875	1929
225/45ZR19	96 XL	Y	300	186	340	49	710	1565
235/45ZR19	99 XL	Y	300	186	340	49	775	1709
245/45ZR19	102 XL	Y	300	186	340	49	850	1874
255/45ZR20	105 XL	Y	300	186	340	49	925	2039
265/45ZR20	104	W	270	168	300	44	900	1984
215/40ZR17	87 XL	Y	300	186	340	49	545	1201
215/40ZR18	89 XL	Y	300	186	340	49	580	1279
225/40ZR18	92 XL	Y	300	186	340	49	630	1389
235/40ZR18	97 XL	Y	300	186	340	49	730	1609
245/40ZR18	97 XL	Y	300	186	340	49	730	1609
255/40ZR18	99 XL	Y	300	186	340	49	775	1709
225/40ZR19	93 XL	Y	300	186	340	49	650	1433
235/40ZR19	96 XL	Y	300	186	340	49	710	1565
245/40ZR19	98 XL	Y	300	186	340	49	750	1653
255/40ZR19	100 XL	Y	300	186	340	49	800	1764
275/40ZR19	101	Y	300	186	300	44	825	1819
245/40ZR20	99 XL	Y	300	186	340	49	775	1709
255/40ZR20	101 XL	W	270	168	340	49	925	2039
255/40ZR21	102 XL	Y	300	186	340	49	850	1874
265/40ZR21	105 XL	Y	300	186	340	49	925	2039
215/35ZR18	84 XL	W	270	168	340	49	500	1102
255/35ZR18	94 XL	Y	300	186	340	49	670	1477
265/35ZR18	97 XL	W	270	168	340	49	730	1609
215/35ZR19	85 XL	W	270	168	340	49	515	1125
225/35ZR19	88 XL	Y	300	186	340	49	560	1235
235/35ZR19	93 XL	Y	300	186	340	49	650	1433
245/35ZR19	97 XL	Y	300	186	340	49	730	1609
255/35ZR19	96 XL	Y	300	186	340	49	710	1565
275/35ZR19	100 XL	Y	300	186	340	49	800	1764
225/35ZR20	93 XL	W	270	168	340	49	650	1433
245/35ZR20	95 XL	Y	300	186	340	49	690	1521
255/35ZR20	97 XL	W	270	168	340	49	730	1609
275/35ZR20	102 XL	Y	300	186	340	49	850	1874
285/35ZR20	104 XL	Y	300	186	340	49	900	1984
295/35ZR20	105 XL	W	270	168	340	49	925	2039
275/35ZR21	103 XL	Y	300	186	340	49	875	1929
255/30ZR19	91 XL	Y	300	186	340	49	615	1356
265/30ZR19	93 XL	W	270	168	340	49	650	1433
275/30ZR19	96 XL	Y	300	186	340	49	710	1565
245/30ZR20	97 XL	W	270	168	340	49	730	1609
275/30ZR20	102 XL	Y	300	186	340	49	850	1874
285/30ZR20	99 XL	W	270	168	340	49	775	1709
275/30ZR21	98 XL	Y	300	186	340	49	750	1653
315/30ZR21	105 XL	Y	300	186	340	49	925	2039



## IMPERO

- Modern design and premium high performance tyre provides sport trucks, SUVs, and crossovers with super handling.
- Confident all-season performance, consistent wear and smooth, quite ride.



## IMPERO

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)
215/65R16	102 XL	H	210	130	340	49	850	1874
215/65R17	99	V	240	149	300	44	775	1709
225/65R17	102	H	210	130	300	44	850	1874
235/65R17	108 XL	V	240	149	340	49	1000	2205
255/65R17	110	H	210	130	300	44	1060	2337
265/65R17	112	H	210	130	300	44	1120	2469
235/65R18	110 XL	H	210	130	340	49	1060	2337
235/60R16	100	V	240	149	300	44	800	1764
215/60R17	96	H	210	130	300	44	710	1565
225/60R17	99	V	240	149	300	44	775	1709
235/60R17	102	H	210	130	300	44	850	1874
225/60R18	104 XL	V	240	149	340	49	900	1984
235/60R18	107 XL	V	240	149	340	49	975	2149
245/60R18	105	V	240	149	300	44	925	2039
255/60R18	112 XL	H	210	130	340	49	1120	2469
265/60R18	110	V	240	149	300	44	1060	2337
275/60R20	115	V	240	149	300	44	1215	2679
235/55ZR17	103 XL	W	270	168	340	49	875	1929
215/55R18	99 XL	V	240	149	340	49	775	1709
235/55R18	100	V	240	149	300	44	800	1764
255/55ZR18	109 XL	W	270	168	340	49	1030	2271
225/55R19	99	V	240	149	300	44	774	1706
235/55ZR19	105 XL	W	270	168	340	49	925	2039
245/55ZR19	103	W	270	168	300	44	875	1929
255/55R19	111 XL	V	240	149	340	49	1090	2403
275/55R19	111	V	240	149	300	44	1090	2403
235/55ZR20	102	W	270	168	300	44	850	1874
255/55R20	110 XL	V	240	149	340	49	1060	2337
275/55ZR20	117 XL	W	270	168	340	49	1285	2833
215/50R18	96 XL	V	240	149	340	49	710	1565
225/50ZR18	99 XL	W	270	168	340	49	775	1709
235/50ZR18	101 XL	W	270	168	340	49	825	1819



**ZTR50**

- Special profile design has been adopted to increase tyre rigidity and driving comfort, high-speed stability and safety.
- Pitch pattern designed by CAD reduces the noise generation.
- Innovative tread compound provides better all-season grip, lower rolling resistance and improved mileage.

Icons: sound off, water droplet, wavy lines, shield, sun.

**ZTR50**

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)	Grade
155/80R13	79	T	190	118	300	44	437	963	D B 70B
155/70R13	79 XL	T	190	118	340	49	437	963	C B 71B
165/70R13	79	T	190	118	300	36	437	963	C B 70B
175/70R13	82	H	210	130	300	44	475	1047	C B 70B
165/70R14	81	T	190	118	300	44	462	1019	C B 70B
175/70R14	88 XL	T	190	118	340	49	560	1235	C B 71B
185/70R14	88	H	210	130	300	44	560	1235	C B 70B
195/70R14	91	H	210	130	300	44	610	1345	C B 70B
165/65R13	77	H	210	130	300	44	412	908	C B 70B
155/65R14	75	T	190	118	300	44	387	853	C B 70B
165/65R14	79	H	210	130	300	44	437	963	C B 70B
175/65R14	86 XL	H	210	130	340	49	530	1168	C B 71B
175/65R14	82	H	210	130	300	44	475	1047	C B 70B
185/65R14	86	H	210	130	300	44	530	1168	C B 70B
175/65R15	88 XL	H	210	130	340	49	560	1235	C B 71B
185/65R15	88	H	210	130	300	44	560	1235	C B 70B
165/60R14	75	H	210	130	300	44	387	853	D B 70B
185/60R14	82	H	210	130	300	44	475	1047	C B 70B
175/60R15	81	H	210	130	300	44	462	1019	C B 70B
185/60R15	88 XL	H	210	130	340	49	560	1235	C B 71B
195/60R15	88	V	240	149	300	44	560	1235	C B 71B
165/55R14	72	H	210	130	300	44	355	783	D B 70B

**ZTR10****ZTR20****ZTR20**

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)	Rating
185/70R13	86	T	190	118	300	44	530	1168	C B 70B
205/70R15	96	H	210	130	300	44	710	1565	B B 71B
215/65R16	98	H	210	130	300	44	750	1653	B B 71B
195/60R14	86	H	210	130	300	44	530	1168	C B 71B
205/60R15	91	V	240	149	300	44	615	1356	B B 71B
175/55R15	77	H	210	130	300	44	412	908	C B 70B
185/55R15	82	V	240	149	300	44	475	1047	C B 70B
185/55R16	83	V	240	149	300	44	487	1074	C B 70B

**ZTR10**

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)	Rating
195/50R16	84	V	240	149	300	44	500	1102	C B 71B
205/50ZR16	87	W	270	168	300	44	545	1201	C B 71B
225/50ZR16	92	W	270	168	300	44	630	1389	B B 71B
205/45ZR16	87 XL	W	270	168	340	49	545	1201	C B 72B
245/45ZR17	99 XL	W	270	168	340	49	775	1709	B B 72B
205/40ZR17	84 XL	W	270	168	340	49	500	1102	C B 72B
245/40ZR17	95 XL	W	270	168	340	49	690	1521	B B 72B

## ZTR08

## ZTR18

- Compact shoulder design to improving stability on shoulder area.
- Special optimized sipes design on mid of tread , provide extra grip capability and braking performance.
- Special tread compound reduces fuel consumption and increases higher mileage.

- Non-directional twists and turn groove new design provides outstanding grip when driving on all season application, even in stony, muddy and off-road condition surfaces.
- Continuous channels ensure faster and more effective water explosion from the contact patch.
- Special tread compound reduces fuel consumption and increases higher mileage.



## ZTR08

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)
185R14C-8PR	102/100	R	170	106	450	65	850	1874
195R14C-8PR	106/104	R	170	106	450	65	950	2094
195R15C-8PR	106/104	S	180	112	450	65	950	2094

C	B	72B	
C	B	72B	
C	B	72B	

## ZTR18

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)
185/75R16C-8PR	104/102	S	180	112	475	69	900	1984
195/75R16C-8PR	107/105	R	170	106	475	69	975	2149
205/75R16C-8PR	110/108	R	170	106	475	69	1060	2337
215/75R16C-8PR	113/111	S	180	112	475	69	1150	2535
175/70R14C-6PR	95/93	S	180	112	375	55	690	1520
195/70R15C-8PR	104/102	S	180	112	450	65	900	1984
215/70R15C-8PR	109/107	S	180	112	475	69	1030	2271
225/70R15C-8PR	112/110	S	180	112	475	69	1120	2469
215/65R15C-6PR	104/102	T	190	118	375	55	900	1984
195/65R16C-8PR	104/102	T	190	118	475	69	900	1984
205/65R16C-8PR	107/105	T	190	118	475	69	975	2149
215/65R16C-8PR	109/107	T	190	118	475	69	1030	2271
225/65R16C-8PR	112/110	T	190	118	475	69	1120	2469
235/65R16C-8PR	115/113	T	190	118	475	69	1215	2679

C	B	72B	

**TOLEDO**    **ZIVARO A/T**

- The tread pattern void ratio is balanced for excellent off-road traction and on road handling.

- High-density siping helps resist hydroplaning by cutting through the thin film of water on the road surface, this provides outstanding all-season traction.

- Wraparound tread gives tyres a rugged look and guards against cuts, bruises and impact breaks, affords outstanding traction especially in muddy or snowy conditions.

- Reinforced wide tread gauge helps to prevent internal damage from impacts sustained when off the road.

- Thick sidewall rubber gauge helps to minimize damage from off-road impact.

- Reinforced carcass and rubber gauge improved hill climbing and steering stability both on and off the road.

**TOLEDO**

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)	Icons
LT235/75R15	110/107	S	180	112	450	65	1060	2337	/ / /
LT265/75R16	123/120 XL	Q	160	100	550	80	1550	3417	/ / /
245/75R16	109	S	180	112	300	44	1030	2271	/ / /
235/70R16	109 XL	T	190	118	340	49	1030	2271	/ / /
245/70R16	111 XL	T	190	118	340	49	1090	2403	/ / /
265/70R16	112	H	210	130	300	44	1120	2469	/ / /
275/65R17	115	H	210	130	300	44	1215	2679	/ / /


**ZIVARO A/T**

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)	Icons
215/70R16	100	H	210	130	300	44	800	1764	/ / /
225/70R16	103	T	190	118	300	44	875	1929	/ / /
225/65R17	102	H	210	130	300	44	850	1874	/ / /
265/65R17	112	T	190	118	300	44	1120	2469	/ / /
265/60R18	114 XL	T	190	118	340	49	1180	2601	/ / /
265/50R20	111 XL	V	240	149	340	49	1090	2403	/ / /
LT215/85R16-10PR	115/112	S	180	112	550	80	1215	2680	/ / /
LT235/85R16-10PR	120/116	Q	160	99	550	80	1380	3042	/ / /
LT235/80R17-10PR	120/117	S	180	112	550	80	1400	3085	/ / /
LT215/75R15-6PR	100/97	S	190	118	550	80	800	1764	/ / /
LT235/75R15-8PR	104/107	S	180	112	450	65	1060	2335	/ / /
LT225/75R16-10PR	115/112	S	180	112	550	80	1215	2680	/ / /
LT245/75R16-10PR	120/116	S	180	112	550	80	1380	3042	/ / /
LT265/75R16-10PR	123/120	S	180	112	550	80	1550	3415	/ / /
LT285/75R16-10PR	126/123	S	180	112	550	80	1700	3750	/ / /
LT245/75R17-10PR	121/118	S	180	112	550	80	1450	3195	/ / /
LT235/70R16-6PR	104/101	S	180	112	350	50	900	1985	/ / /
LT245/70R16-10PR	118/115	S	180	112	550	80	1320	2910	/ / /
LT265/70R16-10PR	121/118	S	180	112	550	80	1450	3195	/ / /
LT245/70R17-10PR	119/116	S	180	112	550	80	1360	3000	/ / /
LT265/70R17-10PR	121/118	S	180	112	550	80	1450	3195	/ / /
LT285/70R17-10PR	121/118	Q	160	99	550	80	1450	3195	/ / /
LT265/70R18-10PR	124/121	S	180	112	550	80	1600	3525	/ / /
LT275/70R18-10PR	125/122	S	180	112	550	80	1650	3640	/ / /
LT275/65R18-10PR	123/120	S	180	112	550	80	1550	3415	/ / /
LT275/65R18-10PR	126/123	S	180	112	550	80	1700	3750	/ / /
LT265/60R20-10PR	121/118	S	180	112	550	80	1450	3195	/ / /
LT285/60R20-10PR	125/122	S	180	112	550	80	1650	3640	/ / /
31*10.5R15LT-6PR	109	S	180	112	350	50	1030	2270	/ / /



## FORTRAK M/T

- Specially designed tread block provide better grip in mud, sand and snow.
- Unique stone-ejector grooves along with a rugged shoulder help to prevent damage from impact.
- Optimized void-to-rubber ratio provides excellent traction.
- Large surface area tread blocks provide increased grip.



### FORTRAK M/T

Size	Loading Index	Speed	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)			
33x12.50R18LT-10PR	118	Q	160	99	450	65	1320	2910	/	/	/
33x12.50R20LT-10PR	114	Q	160	99	450	65	1180	2600	/	/	/
35X12.50R17LT-10PR	121	Q	160	99	450	65	1450	3195	/	/	/
35X12.50R18LT-10PR	123	Q	160	99	450	65	1550	3415	/	/	/
35X12.50R20LT-10PR	121	Q	160	99	450	65	1450	3195	/	/	/
LT285/65R18-10PR	125/122	Q	160	99	550	80	1650	3640	/	/	/



## EV SERIAL TYRE




**ARTORIA EV**

# ARTORIA EV



- Brand-New silent pattern technology, three kinds of computer-optimized varying pitch sequence combined with highly elastic tread formulation idea.
- Adopts super rigidity block for tread central pattern, which not only meets the requirements of high wear mileage, but also provides excellent grip, effectively transferring the huge torque of e-vehicle, and obtain high-speed stability.
- Perfect high bearing capacity. Introduce High load, high safety multiple structure design, to avoid stress concentration, meanwhile optimized each material plus improved liner formulation.
- Tread pattern with high rigid pattern block and high sea-land ratio design, with ultra-low roll resistance formula design, effectively reduce the tire internal energy loss during driving process , so as to reduce rolling energy consumption, improve the endurance mileage of electric vehicles.
- New composite tread material design, creative tread mouth arrangement , upgraded design of crown band layer to strong guarantee ultra-low rolling resistance.



**New**

## ARTORIA EV

Size	Loading Index	Speed	Max. Speed km/h	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)	(C) (C) (C))
255/50ZR20	109 XL	W	270	168	340	49	1030	2271
235/45ZR18	98 XL	Y	300	186	340	49	750	1653
245/45ZR19	102 XL	W	270	168	340	49	850	1874
235/45ZR20	100 XL	W	270	168	340	49	800	1764
255/45ZR19	104 XL	W	270	168	340	49	900	1984
255/45ZR21	105 XL	Y	300	186	340	49	925	2039
235/40ZR19	96 XL	W	270	168	340	49	710	1565
285/40ZR19	107 XL	Y	300	186	340	49	975	2149
255/40ZR20	101 XL	W	270	168	340	49	825	1819
								B A 72B



## ALL-WEATHER TYRES

OUTSTANDING EVERY SEASON



M+S



**ACTIVE 4S**



**ACTIVEPOWER 4S**



**ACTIVEPOWER 4S      ACTIVE 4S**

**ACTIVEPOWER 4S**

- A non-directional all-season tyre for Van and light truck, total balance design to combine with functions and performances.
- Optimized sipes improve excellent wet grip and traction on both hydroplaning and snow road surface.
- Large shoulder block provide strength and stiffness for outstand handling and braking while driving.
- Premium silica compound yields excellent wear and lower rolling-resistance in service.

**ACTIVE 4S**

- A high performance all season tyre with an asymmetric tread design, which has been optimized to provide superior comfort in dry or wet weather and light snow road conditions.
- Multiple sipes across the tread enhance traction in all weather.
- Variable-pitching shoulders design allow for high stability and lower noise.
- A special silica compound leads to increased tread mileage.

Icons: Rain, Snowflake, Sun, Wind, Road, Shield, Bus, Car.

**ACTIVEPOWER 4S**

Size	Ply	Loading Index	Speed	Type	Tread Depth 1/32"	mm	Max. Speed km/h	M+S
195/70R15C	8PR/LRD	104/102	R	Van	12.0	9.5	170	
195/65R16C	8PR/LRD	104/102	R	Van	12.0	9.5	170	
205/65R16C	8PR/LRD	107/105	T	Van	12.0	9.5	190	
215/65R16C	8PR/LRD	109/107	T	Van	12.0	9.5	190	
225/65R16C	8PR/LRD	112/110	S	Van	12.1	9.6	180	
235/65R16C	8PR/LRD	115/113	R	Van	12.2	9.7	170	

**ACTIVE 4S**

Size	Loading Index	Speed	Type	Tread Depth 1/32"	mm	Max. Speed km/h	M+S
165/70R14	81	T	PCR	10.7	8.5	190	
175/70R14	88 XL	T	PCR	10.7	8.5	190	
155/65R14	75	T	PCR	10.7	8.5	190	
175/65R14	82	T	PCR	10.7	8.5	190	
185/65R15	88	H	PCR	10.7	8.5	210	
195/65R15	91	H	PCR	10.7	8.5	210	
215/65R16	102 XL	H	PCR	10.7	8.5	210	
185/60R15	88 XL	H	PCR	10.7	8.5	210	
195/60R15	88	H	PCR	10.7	8.5	210	
205/60R16	96 XL	H	PCR	10.7	8.5	210	
235/60R18	107 XL	V	PCR	10.7	8.5	240	
185/55R15	82	H	PCR	10.7	8.5	210	
195/55R15	85	H	PCR	10.7	8.5	210	
195/55R16	87	H	PCR	10.7	8.5	210	
205/55R16	91	V	PCR	10.7	8.5	240	
215/55R16	97 XL	V	PCR	10.7	8.5	240	
215/55ZR17	98 XL	W	PCR	10.7	8.5	270	
225/55ZR17	101 XL	W	PCR	10.7	8.5	270	
195/50R15	82	V	PCR	10.7	8.5	240	
205/50R17	93 XL	W	PCR	10.7	8.5	270	
225/50R17	98 XL	V	PCR	10.7	8.5	240	
225/45R17	94 XL	V	PCR	10.7	8.5	240	

**ZETA**



## SNOW WITH PASSION

3D-sipes Design With 3rd Generation Silica Tech  
Multi-flat Profile And Wide Tread Design  
Certified Mountain-snowflake Newly  
Introduced Studable  
Winter Tyres Improve Driving Experience On Snow  
As Well As Ice



## WINTER TYRES



**ANTARCTICA 5**

**ANTARCTICA 5 +**

**ANTARCTICA 6**



**ANTARCTICA 8**

**ANTARCTICA ICE**

**ANTARCTICA  
SPORT**



## ANTARCTICA 5

- Designed for excellent comfort, long life and safe trips with short braking distance.
- Specially developed compound and pattern designed for wet and cold road conditions.
- Pattern designed by special simulation programs, and balances water flow and road handling.



**Studless winter tyres for PCR**

<b>ANTARCTICA 5</b>						M+S
Size	Loading Index	Speed	Tread Depth 1/32"	Tread Depth mm	Max. Speed km/h	
155/80R13	79	T	10.6	8.4	190	D D ))71
155/70R13	75	T	10.6	8.4	190	D D ))71
165/70R14	81	T	10.3	8.2	190	D D ))71
175/70R14	88 XL	T	11.0	8.7	190	D D ))71
155/65R13	73	T	10.6	8.4	190	D D ))71
155/65R14	75	T	10.3	8.2	190	D D ))71
175/65R14	82	T	10.7	8.5	190	D D ))71
185/65R14	86	T	10.7	8.5	190	D D ))71
175/65R15	84	T	11.0	8.7	190	D D ))71
185/65R15	88	T	10.7	8.5	190	D D ))71
195/65R15	91	H	10.7	8.5	210	D C ))72
205/65R15	94	H	10.7	8.5	210	D C ))72
215/65R16	98	H	10.7	8.5	210	C C ))72
185/60R14	82	T	10.7	8.5	190	D D ))71
185/60R15	88 XL	H	10.7	8.5	210	D D ))71
195/60R15	88	H	10.7	8.5	210	D C ))72
205/60R16	96 XL	H	10.7	8.5	210	D C ))72
215/60R16	99 XL	H	10.7	8.5	210	C C ))72
185/55R15	82	H	11.0	8.7	210	D D ))71
195/55R15	85	H	10.7	8.5	210	D C ))72
195/55R16	87	H	10.7	8.5	210	D C ))72
205/55R16	91	H	10.7	8.5	210	C C ))72
215/55R16	97 XL	V	10.7	8.5	240	C C ))72
225/55R16	99 XL	V	10.7	8.5	240	C C ))72
205/55R17	95 XL	H	11.0	8.7	210	D C ))72
215/55R17	98 XL	H	10.7	8.5	210	C C ))72
225/55R17	97	H	10.7	8.5	210	C C ))72
205/50R17	93 XL	H	10.7	8.5	240	D C ))72
215/50R17	95 XL	H	11.0	8.7	210	C C ))72
225/50R17	98 XL	H	11.0	8.7	210	C C ))72
195/45R16	84 XL	H	11.0	8.7	210	D C ))72
225/45R17	94 XL	V	10.7	8.5	240	C C ))72
245/45R18	100 XL	V	10.7	8.5	240	C C ))72
225/40R18	92 XL	V	10.7	8.5	240	C C ))72

**ANTARCTICA 5 +**

- Sharp tread management, evacuates water for great wet handling and decreased hydroplaning, also excellent handling performance.
- 100% 3D HD Siping Design will increase snow traction and grip force under heavy cold road conditions.
- Stiff shoulder blocks keep your vehicle stability and curve safety.

**Studless winter tyres for PCR**

**STUDLESS WINTER TYRES**

**M+S**

**New**

**ANTARCTICA 5 +**


Size	Loading Index	Speed	Type	Tread Depth mm	Max. Speed km/h	
165/70R13	79	T	PCR	8	190	
165/70R14	81	T	PCR	8.3	190	
175/70R14	88 XL	T	PCR	8.3	190	
175/65R14	82	T	PCR	8.3	190	
185/65R14	86	H	PCR	8.3	210	
185/65R15	88	H	PCR	8.3	210	
195/65R15	91	H	PCR	8.3	210	
205/65R16	95	T	PCR	8.3	190	
215/65R16	98	H	PCR	8.3	210	
185/60R14	82	H	PCR	8.3	210	
195/60R14	86	T	PCR	8	190	
185/60R15	84	H	PCR	8.3	210	
195/60R15	88	H	PCR	8.3	210	
205/60R16	96 XL	H	PCR	8.3	210	
215/60R16	99 XL	H	PCR	8.3	210	
225/60R16	102 XL	T	PCR	8.3	190	
195/55R15	85	H	PCR	8.3	210	
205/55R16	91	H	PCR	8.3	210	
215/55R16	97 XL	H	PCR	8.3	210	
215/55R17	94	T	PCR	8.3	190	
225/55R17	97	T	PCR	8.3	190	
235/50R18	101 XL	H	PCR	8.3	210	
245/50R18	100	H	PCR	8.3	210	
215/45R16	90 XL	H	PCR	8.3	210	
215/45R17	91 XL	H	PCR	8.3	210	
225/45R17	94 XL	V	PCR	8.3	240	
235/45R17	97 XL	T	PCR	8.3	190	
235/45R18	98 XL	H	PCR	8.3	210	
255/45R18	103 XL	H	PCR	8.3	210	
255/45R19	100	H	PCR	8.3	210	

**ANTARCTICA 6 ANTARCTICA 8****Studless winter tyres for AT/SUV**

- Higher anti-aquaplaning performance design to improves driving stability and safety on wet surface.
- Enough rigidity on shoulder areas to ensure outstanding cross-country performance even on snow or ice.

**Studless winter tyres for VAN**

- Three wide longitudinal grooves provide quick water dispersal and improve handling, braking and hydroplaning resistance.
- The high number of blocks, and high density of 3D sipes, ensure more safety and mobility.
- Drainage grooves on both sides of the shoulder area, work in tandem to effectively drain snow, slush and water, maximizing the tyre's contact with road surface.



M+S



M+S

**ANTARCTICA 6**

Size	Loading Index	Speed	Type	Tread Depth 1/32"	mm	Max. Speed km/h	M+S
215/70R16	100	H	AT/SUV	12.0	9.5	210	C C ))72
245/70R17	110	T	AT/SUV	12.0	9.5	190	C C ))72
235/65R17	108 XL	V	AT/SUV	12.0	9.5	210	C C ))72
245/65R17	107	H	AT/SUV	12.0	9.5	210	C C ))72
215/60R17	96	H	AT/SUV	12.0	9.5	210	D C ))72
225/60R18	100	H	AT/SUV	11.0	8.7	210	C C ))72
235/60R18	107 XL	T	AT/SUV	11.0	8.7	190	C C ))72
235/55R17	103 XL	V	AT/SUV	12.0	9.5	240	D C ))72
215/55R18	95	H	AT/SUV	11.0	8.7	210	C C ))72
225/55R18	98	T	AT/SUV	11.0	8.7	190	C C ))72
235/55R18	104 XL	H	AT/SUV	11.0	8.7	210	C C ))72
255/55R18	109 XL	V	AT/SUV	12.0	9.5	240	C C ))73
235/55R19	101	H	AT/SUV	11.0	8.7	210	C C ))72

**ANTARCTICA 8**

Size	Loading Index	Speed	Type	Tread Depth 1/32"	mm	Max. Speed Km/h	M+S
195/70R15C-8PR	104/102	S	Van	12.5	9.9	180	D C ))73
205/70R15C-8PR	106/104	S	Van	12.5	9.9	180	C D ))73
225/70R15C-8PR	112/110	S	Van	13.0	10.3	180	C C ))73
195/65R16C-8PR	104/102	T	Van	12.5	9.9	190	D C ))73
205/65R16C-8PR	107/105	T	Van	12.5	9.9	190	C D ))73
215/65R16C-8PR	109/107	T	Van	12.5	9.9	190	C C ))73
235/65R16C-8PR	115/113	S	Van	13.0	10.3	180	C C ))73

**ANTARCTICA ICE**

Size	Loading Index	Type	Tread Depth 1/32"	mm	Max. Speed km/h	No.of stud	M+S
205/70R15	100 T XL	PCR	12.0	9.5	190	102	
225/70R16	107 T XL	PCR	13.3	10.5	190	110	
235/70R16	106 T XL	PCR	13.3	10.5	190	112	
245/70R16	111 T XL	PCR	13.3	10.5	190	114	
265/70R16	112 T XL	PCR	13.3	10.5	190	114	
175/65R14	82 T	PCR	12.0	9.5	190	89	
185/65R14	86 T	PCR	12.0	9.5	190	91	
185/65R15	88 T	PCR	12.0	9.5	190	95	
195/65R15	95 T XL	PCR	12.0	9.5	190	97	
205/65R15	99 T XL	PCR	12.0	9.5	190	100	
205/65R16	99 T XL	PCR	12.0	9.5	190	98	
215/65R16	102 T XL	PCR	12.0	9.5	190	105	
185/60R15	88 T XL	PCR	12.0	9.5	190	90	
195/60R15	88 T	PCR	12.0	9.5	190	92	
205/60R16	92 T	PCR	12.0	9.5	190	99	
215/60R16	99 T XL	PCR	12.0	9.5	190	101	
225/60R16	102 T XL	PCR	12.0	9.5	190	103	
195/55R16	91 T XL	PCR	12.0	9.5	190	91	
205/55R16	91 T	PCR	12.0	9.5	190	96	
215/55R16	97 T XL	PCR	12.0	9.5	190	100	
215/55R17	94 T	PCR	12.0	9.5	190	100	
225/55R17	97 T	PCR	12.0	9.5	190	100	
225/50R17	98 H XL	PCR	12.0	9.5	210	100	
225/45R17	94 H XL	PCR	12.0	9.5	210	97	
245/45R18	100 H XL	PCR	12.0	9.5	210	98	
225/40R18	92 H XL	PCR	12.0	9.5	210	97	



## ANTARCTICA SPORT

- V-sharp directional studdable tread design integrated more comfort and safer drive on ice/snow surface.
- Advanced high elasticity tread rubber compound formulation fitted for a very low temperature.
- Enhances grip capacity and traction performance on heavy icy road optimized stud pin position combined with multi-sipe groove arrangement.



Studable winter tyres for AT/SUV/LT/Van



### ANTARCTICA SPORT

Size	Loading Index	Type	Tread Depth 1/32"	mm	Max. Speed km/h	No.of stud	M+S
215/70R16	100 T	SUV	13.3	10.5	190	109	C C ))72
265/70R17	115 S	SUV	13.3	10.5	180	115	C C ))73
215/65R17	103 TXL	SUV	13.3	10.5	190	107	C C ))72
225/65R17	102 T	SUV	13.3	10.5	190	111	D C ))72
235/65R17	108 TXL	SUV	13.3	10.5	190	113	C C ))72
265/65R17	116 TXL	SUV	13.3	10.5	190	113	C C ))73
215/60R17	96 T	SUV	13.3	10.5	190	105	D C ))72
225/60R17	103 TXL	SUV	13.3	10.5	190	107	C C ))72
265/60R18	114 TXL	SUV	12.0	9.5	190	113	C C ))73
275/60R20	115 S	SUV	13.3	10.5	180	120	C C ))73
255/55R18	109 TXL	SUV	12.0	9.5	190	106	C C ))73
225/55R19	103 TXL	SUV	12.0	9.5	190	111	C C ))72
275/55R20	117 H XL	SUV	13.3	10.5	210	120	C C ))73
285/50R20	116 TXL	SUV	13.3	10.5	190	117	C C ))75
275/50R21	113 TXL	SUV	13.3	10.5	190	120	C C ))73
235/45R18	98 T XL	SUV	12.0	9.5	190	102	C C ))72
245/45R20	103 H XL	SUV	13.3	10.5	210	111	C C ))72
275/40R20	106 TXL	SUV	13.3	10.5	190	108	C C ))73
315/35R20	110 TXL	SUV	13.3	10.5	190	108	C C ))75
LT225/75R16-10PR	115/112 Q	LT	13.3	10.5	160	115	C C ))73
LT245/75R16-10PR	120/116 Q	LT	13.3	10.5	160	113	C C ))73
LT265/70R17-10PR	121/118 Q	LT	13.3	10.5	160	115	C C ))73
235/65R16C-8PR	115/113 R	Van	13.6	10.7	170	109	C C ))73
235/65R16C-10PR	121/119 R	Van	13.6	10.7	170	109	C C ))73

ZETA



## RUN-FLAT

A true new generation of run-flat tyres



ALVENTI

IMPERO

ACCENI

**New**
**ACCENi    ALVENTI    IMPERO**
**ZETA Run-flat Tyre Specifications**

Size	Loading Index	Speed	Pattern Code	Max. Speed km/h	Max. Speed MPH	Max. Pressure S(kPa)	Max. Pressure S(psi)	Max. Load S(kg)	Max. Load S(lb)
205/60ZRF16 RFT	92	W	ALVENTI	270	168	300	44	630	1389
195/55ZRF16 RFT	87	V	ALVENTI	240	149	300	44	545	1201
205/55ZRF16 RFT	91	W	ALVENTI	270	168	300	44	615	1356
225/55ZRF16 RFT	95	W	ALVENTI	270	168	300	44	690	1521
205/50ZRF17 RFT	91	V	ALVENTI	240	149	300	44	615	1356
225/55ZRF17 RFT	97	Y	ALVENTI	300	186	300	44	730	1609
205/50ZRF17 RFT	89	W	ALVENTI	270	168	300	44	580	1279
225/50ZRF17 RFT	94	W	ALVENTI	270	168	300	44	750	1653
205/45ZRF17 RFT	88 XL	W	ALVENTI	270	168	340	49	560	1235
225/45ZRF17 RFT	94 XL	W	ALVENTI	270	168	340	49	670	1477
225/45ZRF18 RFT	91	Y	ALVENTI	300	186	300	44	615	1356
245/45ZRF18 RFT	96	Y	ALVENTI	300	186	300	44	810	1786
255/45ZRF18 RFT	103 XL	Y	ALVENTI	300	186	340	49	875	1929
225/45ZRF19 RFT	92	W	ALVENTI	270	168	340	49	710	1565
235/45RF19 RFT	95	V	ALVENTI	240	149	300	44	690	1521
245/45ZRF19 RFT	102 XL	Y	ALVENTI	300	186	340	49	850	1874
255/45ZRF20 RFT	105 XL	W	ALVENTI	270	168	340	49	925	2039
215/40ZRF18 RFT	85	Y	ALVENTI	300	186	300	44	515	1135
225/40ZRF18 RFT	92 XL	Y	ALVENTI	300	186	340	49	630	1389
235/40ZRF18 RFT	95 XL	W	ALVENTI	270	168	340	49	690	1521
245/40ZRF18 RFT	93	Y	ALVENTI	300	186	300	44	650	1433
255/40ZRF18 RFT	95	W	ALVENTI	270	168	300	44	690	1521
225/40ZRF19 RFT	93 XL	Y	ALVENTI	300	186	340	44	650	1433
245/40ZRF19 RFT	98 XL	Y	ALVENTI	300	186	340	49	750	1653
255/40ZRF19 RFT	100 XL	Y	ALVENTI	300	186	340	49	800	1764
275/40ZRF19 RFT	101	Y	ALVENTI	300	186	300	44	825	1819
245/40ZRF20 RFT	99 XL	Y	ALVENTI	300	186	340	49	775	1709
255/35ZRF18 RFT	90	Y	ALVENTI	300	186	300	44	600	1323
255/35ZRF19 RFT	96 XL	Y	ALVENTI	300	186	340	49	710	1565
275/35ZRF19 RFT	100 XL	Y	ALVENTI	300	186	340	49	800	1764
275/35ZRF20 RFT	102 XL	Y	ALVENTI	300	186	340	49	850	1874
275/35ZRF21 RFT	103 XL	W	ALVENTI	270	168	340	49	875	1929
225/60RFT17 RFT	99	V	IMPERO	240	149	300	44	775	1709
235/60RFT18 RFT	107 XL	V	IMPERO	240	149	340	49	975	2149
235/55ZRF18 RFT	100	W	IMPERO	270	168	300	44	800	1764
255/55RF18 RFT	109 XL	V	IMPERO	240	149	340	49	1030	2271
235/55RF19 RFT	101	V	IMPERO	240	149	300	44	825	1819
225/50ZRF18 RFT	95	W	IMPERO	270	168	300	44	690	1521
235/50ZRF18 RFT	101 XL	W	IMPERO	270	168	340	49	825	1819
245/50ZRF18 RFT	100	Y	IMPERO	300	186	300	44	800	1764
245/50ZRF19 RFT	105 XL	W	IMPERO	270	168	340	49	925	2039
255/50ZRF19 RFT	103	W	IMPERO	270	168	300	44	875	1929
265/50ZRF19 RFT	110 XL	Y	IMPERO	300	186	340	49	1060	2337
275/50RFT20 RFT	113 XL	V	IMPERO	240	149	340	49	1150	2535
285/45ZRF19 RFT	107	W	IMPERO	270	168	300	44	975	2149
245/45ZRF20 RFT	103 XL	W	IMPERO	270	168	340	49	875	1929
275/45ZRF20 RFT	110 XL	W	IMPERO	270	168	340	49	1060	2337
285/45ZRF21 RFT	113 XL	W	IMPERO	270	168	340	49	1150	2535
275/40ZRF20 RFT	106 XL	W	IMPERO	270	168	340	49	950	2094
305/40ZRF20 RFT	112 XL	W	IMPERO	270	168	340	49	1120	2469
275/40ZRF21 RFT	107 XL	W	IMPERO	270	168	340	49	975	2149
315/35ZRF20 RFT	110 XL	W	IMPERO	270	168	340	49	1060	2337
315/35ZRF21 RFT	111 XL	W	IMPERO	270	168	340	49	1090	2403
275/35ZRF21 RFT	103 XL	W	ACCENi	270	168	340	49	875	1929
275/40ZRF18 RFT	103 XL	W	ACCENi	270	168	340	49	875	1929

RFT (RSC)



D B 71B

C B 69B

B A 70B

D B 71B

D B 73B

TBA TBA TBA

TBA TBA TBA

**ZETA**

