

HOW TO SELECT A TYRE

Consult Vehicle Owner's Manual or Door Placard for Proper Tyre Size and Load/Speed Index
Consider Average Vehicle Usage (Extended Highway Use, Off-Road, etc.)

MOUNTING/DISMOUNTING/SERVICE

Only Allow Trained Professionals to Mount, Dismount, or Service Your Tyres.

TYRE PRESSURE

Consult Vehicle Owner's Manual or Door Placard for Proper Pressure for Your Vehicle.
PSI/kg Indicted on Sidewall is the Maximum for the Tyre, Which May Not Be Proper for Your Vehicle.
Check/Adjust Pressure when Tyres Are Cold.

CHECK THE FOLLOWING ITEMS MONTHLY

TREAD AREA

Uneven Wear, Cuts, Bulges, Foreign Objects

SIDEWALL

Ozone Cracking, Cuts, Bulges, Impact Damage



IF ANY OF THESE CONDITIONS EXIST – CONSULT A PROFESSIONAL IMMEDIATELY.

www.zeta-tyres.com

DISTRIBUTED BY

www.sd-international.com

These data can be changed by the manufacturer without prior notice and differently applied by regions.

Printed on Apr. 2026



CHOOSE ZETA AND TAKE CONTROL

Made In Thailand



ZETA



2026 ZETA TYRES LINE UP

P.3	HP	VERDANT
P.5	HP	VENTTI 3
P.7	UHP	VENTTI 5
P.9	CUV	ETALON
P.11	SUV	IMPERO
P.15	EV	ARTORIA EV
P.17	RT	PANTHER CLAW R/T <i>POR</i>
P.19	VAN	CITY TRANS



VERDANT



Quietness



Comfort



Safety



Advanced tread design

An advanced tread design coupled with a high stylized sidewall design offers excellent driving comfort.

Equilibrium carcass structure

Equilibrium polyester body ply, wider steel belts plus high density jointless nylon full cover minimize tyre deformation, enhance durability and stability.

Silica compound

Silica compound provides improved dry & wet traction along with lower rolling resistance.

VERDANT

Size	LI/SI	UTQG	TD mm	Load Capacity Kg	DUAL LOAD		Max.Speed km/h			
185/70R14	88 H	500AA	7.8	560	/	/	210	C	B	68 B
195/70R14	91 H	500AA	8.0	615	/	/	210	C	B	69 B
205/70R15	96 H	500AA	8.0	710	/	/	210	C	B	69 B
215/70R15	98 H	500AA	8.3	750	/	/	210	C	B	69 B
165/65R14	79 H	500AA	7.8	437	/	/	210	D	C	68 B
175/65R14	84 T XL	500AA	7.8	500	/	/	190	D	C	69 B
185/65R14	86 H	500AA	7.8	530	/	/	210	C	B	68 B
175/65R15	88 H XL	500AA	7.8	560	/	/	210	C	C	69 B
185/65R15	88 H	500AA	7.8	560	/	/	210	C	B	68 B
195/65R15	91 V	500AA	8.0	615	/	/	240	C	B	69 B
205/65R15	94 H	500AA	8.0	670	/	/	210	C	B	69 B
205/65R16	95 V	500AA	7.8	690	/	/	240	C	B	69 B
215/65R16	98 H	500AA	8.0	750	/	/	210	C	B	69 B
185/60R14	82 H	500AA	7.8	475	/	/	210	D	B	68 B
195/60R14	86 H	500AA	8.0	530	/	/	210	C	B	69 B
165/60R15	77 H	500AA	7.8	412	/	/	210	D	C	68 B
185/60R15	88 H XL	500AA	7.8	560	/	/	210	C	B	69 B
195/60R15	88 V	500AA	8.0	560	/	/	240	C	B	69 B
205/60R15	91 V	500AA	8.0	615	/	/	240	C	B	69 B
205/60R16	92 V	500AA	8.0	630	/	/	240	C	B	69 B
215/60R16	95 V	500AA	8.3	690	/	/	240	C	B	69 B
225/60R16	98 H	500AA	8.3	750	/	/	210	C	B	69 B
165/55R14	72 H	500AA	7.8	355	/	/	210	D	C	68 B
185/55R15	82 V	500AA	7.8	475	/	/	240	D	B	68 B
195/55R15	85 V	500AA	8.0	515	/	/	240	D	B	69 B
195/55ZR16	91 W XL	500AA	8.0	615	/	/	270	C	B	70 B
205/55R16	91 V	500AA	8.0	615	/	/	240	C	B	69 B
215/55R16	97 V XL	500AA	8.0	730	/	/	240	C	B	70 B
225/55ZR16	99 W XL	500AA	8.0	775	/	/	270	C	B	70 B
195/50R15	82 V	500AA	8.0	475	/	/	240	D	B	69 B
205/50ZR16	87 W	500AA	8.0	545	/	/	270	C	B	69 B
205/45ZR16	87 W XL	500AA	8.0	545	/	/	270	C	B	70 B



VENTTI3



Saving



Wear Resistance



Anti-slip



Fuel-saving compound

The new rubber compound of the Ventti 3 improves fuel efficiency by reducing rolling resistance.

Superior water evacuation

The four wide circumferential grooves and lateral grooves work together to enhance the tyre's water drainage performance.

Heat-resistant shoulder

The tyre shoulder is fully equipped with heat-resistant features that help keep the tread blocks stable.

VENTTI3

Size	LI/SI	UTQG	TD		Load Capacity		Max.Speed	
			mm	32nds	Kg	lbs	km/h	mph
155/65R14	75T	500 A A	7.8	9.8	387	853	190	118
165/60R14	75H	500 A A	7.8	9.8	387	853	210	130
165/70R14	81T	500 A A	7.8	9.8	462	1019	190	118
175/70R14	88H XL	500 A A	7.8	9.8	560	1235	210	130
215/55R17	98W XL	500 A A	8.0	10.1	750	1653	270	168
215/55R18	99V XL	500 A A	8.0	10.1	775	1709	240	149
225/40R18	92W XL	500 A A	8.0	10.1	630	1389	270	168
225/45R18	95W XL	500 A A	8.0	10.1	690	1521	270	168
225/50R18	99W XL	500 A A	8.0	10.1	775	1709	270	168
225/55R17	101W XL	500 A A	8.0	10.1	825	1819	270	168
225/60R18	104V XL	500 A A	8.0	10.1	900	1984	240	149
235/55R17	103W XL	500 A A	8.3	10.4	870	1929	270	168



VENTTI 5



Anti-slip



Outstanding Handling



Excellent Grip



Advanced LS silica technology

Specially formulated LS Silica Compound enhances performance by increasing flexibility in low temperatures and improving traction on wet surfaces, providing greater control. Reduced rolling resistance also contributes to improved fuel efficiency.

Compact rigid shoulder

The compact shoulder design improves stability in the shoulder area for more confident handling.

Anti-hydroplaning grooves

Four longitudinal performance main grooves deliver excellent water evacuation, enhanced wet braking performance, and increased resistance to hydroplaning.

VENTTI 5

Size	LI/SI	UTQG	TD		Load Capacity		Max.Speed	
			mm	32nds	Kg	lbs	km/h	mph
205/40R17	84W XL	500 A A	8.0	10.1	500	1102	270	168
205/45R17	88W XL	500 A A	8.0	10.1	560	1235	270	168
205/50R17	93W XL	500 A A	8.0	10.1	650	1433	270	168
215/40R17	87W XL	500 A A	8.0	10.1	545	1202	270	168
215/45R17	91W XL	500 A A	8.0	10.1	615	1356	270	168
215/45R18	89W	500 A A	8.0	10.1	580	1279	270	168
215/50R17	95W XL	500 A A	8.0	10.1	690	1521	270	168
225/35R19	88W XL	500 A A	8.0	10.1	560	1235	270	168
225/35R20	90W XL	500 A A	8.0	10.1	600	1323	270	168
225/45R17	94W XL	500 A A	8.0	10.1	670	1477	270	168
225/45R19	96W XL	500 A A	8.0	10.1	710	1565	270	168
225/50R17	98W XL	500 A A	8.0	10.1	750	1653	270	168
225/55R18	102W XL	500 A A	8.0	10.1	850	1874	270	168
235/35R19	91W XL	500 A A	8.0	10.1	615	1356	270	168
235/40R18	95W XL	500 A A	8.0	10.1	690	1521	270	168
235/45R17	97W XL	500 A A	8.0	10.1	730	1609	270	168
245/35R19	97W XL	500 A A	8.0	10.1	730	1609	270	168
245/35R20	95W XL	500 A A	8.0	10.1	690	1521	270	168
245/40R18	97W XL	500 A A	8.0	10.1	730	1609	270	168
245/40R19	98W XL	500 A A	8.0	10.1	750	1653	270	168
245/40R20	99W XL	500 A A	8.0	10.1	775	1709	270	168
245/45R17	99W XL	500 A A	8.0	10.1	775	1709	270	168
245/45R18	100W XL	500 A A	8.0	10.1	800	1764	270	168
245/45R19	102Y XL	500 A A	8.0	10.1	850	1874	300	186
245/50R18	100W	500 A A	8.0	10.1	800	1764	270	168
245/50R20	102W	500 A A	8.0	10.1	850	1874	270	168
255/35R18	94W XL	500 A A	8.0	10.1	670	1477	270	168
255/35R19	96W XL	500 A A	8.0	10.1	710	1565	270	168
255/35R20	97W XL	500 A A	8.0	10.1	730	1609	270	168
255/40R19	100W XL	500 A A	8.0	10.1	800	1764	270	168
255/45R18	99W	500 A A	8.0	10.1	775	1709	270	168
255/50R19	103W	500 A A	8.0	10.1	875	1929	270	168
255/50R20	109Y XL	500 A A	8.0	10.1	1030	2271	300	186
265/35R18	97W XL	500 A A	8.0	10.1	730	1609	270	168
265/45R20	104W	500 A A	8.0	10.1	900	1984	270	168
265/50R19	110Y XL	500 A A	8.0	10.1	1060	2337	300	186
265/50R20	111W XL	500 A A	8.0	10.1	1090	2403	270	168
275/30R20	97W XL	500 A A	8.0	10.1	730	1609	270	168
275/35R19	100W XL	500 A A	8.0	10.1	800	1764	270	168
275/40R19	101Y	500 A A	8.0	10.1	825	1819	300	186
275/55R19	111V	500 A A	8.3	10.4	1090	2403	240	149
275/60R20	115V	500 A A	8.3	10.4	1215	2679	240	149
285/35R21	105V XL	500 A A	8.3	10.4	925	2039	240	149
285/45R19	107W	500 A A	8.3	10.4	975	2150	270	168
285/50R20	116V XL	500 A A	8.3	10.4	1250	2756	240	149
295/35R21	107V XL	500 A A	8.3	10.4	975	2150	240	149



ETALON



Quietness



Wear Resistance



Anti-slip



Low Rolling Resistance



Excellent all-weather handling

Etalon gives you the all weather handling you need for your crossover vehicle, while delivering a comfortable and quiet ride.

Circumferential zigzag grooves

Circumferential zigzag grooves resist hydroplaning by channeling water away from the tread.

Optimized tread profile design

Optimized tread profile design reduces rolling resistance significantly and increases fuel efficiency.

Integrated shoulder

Integrated shoulder minimizes road noise and uneven wear for quite ride.

ETALON

Size	LI/SI	UTQG	TD mm	Load Capacity Kg	DUAL LOAD Kg lbs		Max.Speed km/h			
235/75R15	105 H	500AA	8.3	925	/	/	210	C	B	71 B
215/70R16	100 H	500AA	8.0	800	/	/	210	C	B	71 B
225/70R16	103 H	500AA	8.0	875	/	/	210	C	B	71 B
235/70R16	106 H	500AA	8.0	950	/	/	210	C	B	71 B
245/70R16	111 T XL	500AA	8.0	1090	/	/	190	C	B	72 B
255/70R16	111 T	500AA	8.3	1090	/	/	190	C	B	72 B
265/70R16	112 T	500AA	8.3	1120	/	/	190	C	B	72 B
245/70R17	110 T	500AA	8.3	1060	/	/	190	C	B	71 B
265/70R17	115 S	500AA	8.3	1215	/	/	180	C	B	72 B
235/65R16	103 H	500AA	8.0	875	/	/	210	C	B	71 B
215/65R17	99 H	500AA	8.0	775	/	/	210	C	B	71 B
225/65R17	102 H	500AA	8.0	850	/	/	210	C	B	71 B
235/65R17	108 V XL	500AA	8.0	1000	/	/	240	C	B	72 B
245/65R17	111 H XL	500AA	8.0	1090	/	/	210	C	B	72 B
265/65R17	112 H	500AA	8.0	1120	/	/	210	C	B	72 B
235/65R18	110 H XL	500AA	8.0	1060	/	/	210	C	B	72 B
265/65R18	114 H	500AA	8.0	1180	/	/	210	C	B	72 B
275/65R18	116 H	500AA	8.0	1250	/	/	210	C	B	72 B
215/60R17	96 H	500AA	8.0	710	/	/	210	C	B	71 B
225/60R17	99 V	500AA	8.3	775	/	/	240	C	B	71 B
235/60R17	106 V XL	500AA	8.3	950	/	/	240	C	B	72 B
235/60R18	107 V XL	500AA	8.0	975	/	/	240	C	B	72 B
265/60R18	110 V	500AA	8.0	1060	/	/	240	C	B	72 B
235/55R18	100 V	500AA	8.0	800	/	/	240	C	B	71 B
255/55R18	109 V XL	500AA	8.0	1030	/	/	240	C	B	73 B



IMPERO



Quietness



Comfort



Excellent Grip



Low Rolling Resistance



SUV

Wide longitudinal grooves

4 wide longitudinal grooves improves drainage performance.

Anti-hydroplaning lateral grooves

Anti-hydroplaning lateral grooves offers excellent wet performance.

Center block

3 center block provide straight-driving stability.

Optimized shoulder blocks

Optimized shoulder blocks maximize grip during cornering.

IMPERO

Size	LI/SI	UTQG	TD mm	Load Capacity Kg	DUAL LOAD Kg lbs		Max.Speed km/h			
235/55ZR19	105 W XL	500AA	8.0	905	/	/	270	B	B	71 B
255/55R19	111 V XL	500AA	8.0	1090	/	/	240	B	B	72 B
235/55ZR20	105 W XL	500AA	8.0	905	/	/	270	B	B	71 B
275/55ZR20	117 W XL	500AA	8.3	1285	/	/	270	B	B	72 B
275/50R22	115 H XL	500AA	8.3	1215	/	/	210	B	B	72 B
245/45ZR20	103 W XL	500AA	8.0	875	/	/	270	B	B	71 B
255/45ZR20	105 W XL	500AA	8.0	925	/	/	270	B	B	72 B
275/45R20	110 V XL	500AA	8.3	1060	/	/	240	B	B	72 B
285/45R22	114 V XL	500AA	8.3	1180	/	/	240	B	B	74 B
305/45R22	118 V XL	500AA	8.3	1320	/	/	240	B	B	74 B
275/40ZR20	106 W XL	500AA	8.3	950	/	/	270	B	B	72 B
305/40R22	114 V XL	500AA	8.3	1180	/	/	240	B	B	74 B
265/40ZR22	106 W XL	500AA	8.3	950	/	/	270	B	B	72 B
285/40ZR22	110 Y XL	500AA	8.3	1060	/	/	300	B	B	74 B
275/35ZR20	102 Y XL	500AA	8.0	850	/	/	300	B	B	72 B
265/35ZR22	102 W XL	500AA	8.0	850	/	/	270	B	B	72 B
285/35ZR22	106 W XL	500AA	8.3	950	/	/	270	B	B	74 B
275/35ZR24	106 W XL	500AA	8.0	950	/	/	270	B	B	72 B
295/35R24	110 V XL	500AA	8.0	1060	/	/	240	B	B	74 B
305/35ZR24	112 W XL	500AA	8.3	1120	/	/	270	B	B	74 B
315/35ZR20	110 W XL	500AA	8.3	1060	/	/	270	B	B	74 B
235/30ZR22	90 W XL	500AA	8.3	600	/	/	270	C	B	71 B
245/30ZR22	95 W XL	500AA	8.0	690	/	/	270	C	B	71 B
255/30ZR24	97 W XL	500AA	8.0	730	/	/	270	C	B	72 B
295/25ZR22	97 W XL	500AA	8.0	730	/	/	270	C	B	74 B

ARTORIA EV



Quietness



Comfort



Anti-slip



Fuel Efficiency



Brand-New Silent pattern Technology

Brand-new silent pattern technology features three computer-optimized variable pitch sequences combined with a highly elastic tread compound concept.

Adopts super rigidity block

Adopts super-rigid tread blocks in the central pattern, which not only meet high mileage wear requirements but also provide excellent grip, effectively transferring the high torque of electric vehicles and ensuring high-speed stability.

Perfect high bearing capacity

Introduces a multi-structure design for high load and safety to avoid stress concentration, while optimizing material distribution and improving the inner liner formulation.

New composite tread material design

New composite tread material design, creative tread groove arrangement, upgraded design of crown band layer to strongly guarantee ultra-low rolling resistance.

Tread pattern with high rigid pattern block

Tread pattern with high rigid pattern block and high void ratio design, with ultra-low rolling resistance formula design, effectively reduce the tyre internal energy loss during driving process, so as to reduce rolling energy consumption, improve the endurance mileage of electric vehicles.

ARTORIA EV

Size	LI/SI	UTQG	TD mm	Load Capacity Kg	DUAL LOAD Kg lbs		Max.Speed km/h			
235/45ZR18	98 Y XL	380AA	7.0	750	/	/	300	C	A	70 B
255/45ZR19	104 Y XL	380AA	7.0	900	/	/	300	B	B	71 B
235/40ZR19	96 W XL	380AA	7.0	710	/	/	270	C	B	70 B
285/40ZR19	107 Y XL	380AA	7.0	975	/	/	300	C	A	73 B
255/40ZR20	101 Y XL	380AA	7.0	825	/	/	300	B	B	71 B





On/Off-The-Road

ANTHER CLAW R/T **POR**

Beyond All Terrain

Positioned between on-road and off-road, RT tyres deliver a balanced approach to traction, durability, and everyday usability.





PANTHER CLAW R/T

POR



Outstanding Handling



Anti-impact



Wear Resistance



Excellent Grip



RT



3PLY
Sidewall Puncture Guard
M+S
RATED

Optimized tread pitch design

Technologically advanced computer modeling for optimized tread pitch variation, perfectly placed tread sipes, and tread block alignment greatly reduce noise, providing a more refined, comfortable, smooth, quiet ride.

Enhanced damage-resistant tread compound

Enhanced fatigue resistant tread compound protects tyre from chips/cuts/rocks/other debris, ensuring extended tyre life by preventing premature failure in off-road use.

High-strength steel belts

The sidewalls of the rogueblazer are equipped with three layers of polyester cord fabric and high-strength steel belts to combat sharp debris and rocks.

Ultra-stable shoulder technology

Ultra-stable shoulder technology, the shifting shapes of the large shoulder blocks are designed for improved handling and control through dirt, mud, sand and snow.

PANTHER CLAW R/T **POR**

Size	LI/SI	UTQG	Category	TD mm	Load Capacity	DUAL LOAD		Max.Speed
					Kg	Kg	lbs	km/h
LT235/80R17-10	120/117 Q	/	RT (POR)	13.0	1400	1285	2835	160
LT285/70R17-10PR	121/118 Q	/	RT (POR)	15.5	1450	1320	2910	160
LT265/60R20-10PR	121/118 Q	/	RT (POR)	13.5	1450	1320	2910	160
LT275/55R20-10PR	120/117 Q	/	RT (POR)	14.5	1400	1285	2835	160
33X12.50R17LT-12PR	121 Q	/	RT (POR)	15.5	1450	/	/	160
35X12.50R17LT-12PR	121 Q	/	RT (POR)	15.7	1450	/	/	160
33X12.50R20LT-12PR	119 Q	/	RT (POR)	15.4	1360	/	/	160
33X12.50R22LT-12PR	114 Q	/	RT (POR)	15.5	1180	/	/	160
35X12.50R22LT-12PR	121 Q	/	RT (POR)	15.5	1450	/	/	160



CITY TRANS



Outstanding
Handling



Wear
Resistance



Low Rolling
Resistance



New generation with high void ratio design

A new generation with high void ratio design, better pressure resistance, and deep zigzag pattern grooves with good wear resistance.

More full siping design

A more fully siped design helps maintain wet traction by effectively channeling water away from the contact area.

All-season performance and handling

The continuous zigzag middle 4-rib design improves straight-line stability and turning maneuverability.

CITY TRANS

Size	LI/SI	UTQG	TD mm	Load Capacity Kg	DUAL LOAD		Max.Speed km/h			
195/75R16C-10PR	110/108 R	/	8.8	1060	1000	2205	170	C	C	72 B
185/60R15C-8PR	94/92 T	/	8.8	670	630	1390	190	C	C	72 B
235/65R16C-12PR	121/119 R	/	8.8	1450	1360	3000	170	C	C	72 B